Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	6370	(master with (read$5 or scan$5)) and (slave with (read$5 or scan$5))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:46
L2	319	1 and ((designat$5) near3 (master)) and ((designat$5) near3 (slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:46
L3	52	2 and ((read$5 or scan$6) near3 (setting or condition))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:46
L4	27665	((master or slave) with (read$5 or scan$5))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:47
L5	453	4 and ((designat$5) near3 (master)) and ((designat$5) near3 (slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:47
L6	61	5 and ((read$5 or scan$6) near3 (setting or condition))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:48
L7	69171	((master or slave) with (read$5 or scan$5 or print$5 or output$5))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:47
L8	730	7 and ((designat$5) near3 (master)) and ((designat$5) near3 (slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:48
L9	72	8 and ((read$5 or scan$6) near3 (setting or condition))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:48
L10	794	7 and ((designat$5 or specif$8) near3 (master)) and ((designat$5) near3 (slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:48

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	13274	(358/1.2,1.9,1.15,401,407,444,448.ccls.)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:13
L2	1615	399/48,85,82,81.ccls.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:13
L3	449	(1 or 2 or (700/3.ccls.) or (709/208, 209.ccls.)) and (master same slave same (read$5 or scan$5 or print$5))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:15
L4	155	3 and ((designat$5 or specif$7) near3 (master or slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:15
L5	187	3 and ((designat$5 or specif$7 or assign$7) near3 (master or slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:15
L6	5	5 and ((read$5 or scan$6) near3 (setting or condition) with slave)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:17
L7	5	5 and ((read$5 or scan$6) near3 (setting or condition) with (master or slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:17

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L11	58	matsuda-yoji.in.	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:36
L12	1	11 and ((designat$5 or specif$8 or assign$6) near3 (master or slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:37
L13	1	11 and ((designat$5 or specif$8 or assign$6) near8 (master or slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 15:37

L11	1434	7 and ((designat$5 or specif$8) near3 (master)) and ((designat$5 or specif$8) near3 (slave))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:48
L12	141	11 and ((read$5 or scan$6) near3 (setting or condition))	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2005/09/02 13:48